

Emergency LED T8 Batten



Features:

- Aluminum housing and PC cover
- Taiwan SMD LED chips
- High Lumen output
- Voltage: AC 220-240V, 50Hz
- Power factor: >0.95
- Lumen per watt: 100lm/W
- Lumen: 800lm for 600mm LED T8 tube and 1800lm for 1200mm LED T8 tube
- Life time: 50000 hours
- Color rendering index: >80
- Color temperature range from 3000-3200K, 4000-4500K, 5600-6500K
- Lamp base: G13
- Industry British style batten
- Dimension: 600mm and 1200mm
- Rechargeable Ni-Cad battery
- Full charge: 12 hours
- Discharge : >2 hours
- 100% DC emergency output
- Meeting international safety standard EN60598 and EMC standard EN61000-3-2, EN61000-3-3, EN55015, EN61547
- CE standard and RoHS
- Country of origin: PRC
- Tested by Hong Kong Polytechnic University
- Comply with the requirement of Hong Kong Fire Service Department
- Comply with BS-5266-Part 1,-BS 5499-3:1990, BSEN60598-2-22, (850°C hot wire test)
- FSD COP Clause 5.10, FSD PPA 104A 4th Rev, Electricity of Ordinance (Cap.406)
- Code of Practice for Electricity (Wiring) Regulations

Specifications:

| Model | Voltage | Power | Lumen | Color temp | Dimension | Life time |
|--------------|------------|-------|---------|------------|-----------|--------------|
| LED T8-600E | AC220-240V | 8W | 800 lm | 3000-6500K | 600mm | 50,000 hours |
| LED T8-1200E | AC220-240V | 18W | 1800 lm | 3000-6500K | 1200mm | 50,000 hours |