

LED Exit Sign



Features

- GMS casing with white power coating
- Built in Taiwan LED chips
- Each chips work independently
- 3-4W
- Rated supply voltage: 180V-250V
- 50000 hours life time
- Charging time<12 hours
- Discharging time: 3 hours
- Dimension: 450-650mm in length
- Test report from Hong Kong Polytechnic University
- Comply with the regulation of Hong Kong Fire Service Department

Standards:

- BS-5266-Part 1
- BS 5499-3:1990
- IEC-60598-2-22
(850°C hot wire test)
- FSD COP Clause 5.10
- FSD PPA 104A 4th Revision
- Electricity of Ordinance
(Cap.406)
- Code of Practice for Electricity
(Wiring) Regulations

Applications

Shopping, Residential area, commercial bldg, Factory, etc.,

Specifications

Voltage	180V-250V AC	180C-250V
Power	4W	4W
Battery	Ni-Cad	Ni-Cad
Charge time	Within 12 hours	Within 12 hours
Discharge time	3 hours	3 hours
Dimension	630mm x 75mm x 55mm (base)	650mm x 180mm x 50mm
Plate size	570mm x 160mm x 10mm	NIL
Type	LED exit sign plate	LED exit sign box
Standard	BS 5266, IEC 60598-2-22, FSD PPA 104A (4th revision)	