

# LED T5 Batten with diffuser



## Features:

- Save up to 60% energy
- A grade SMD LED chips
- Light efficiency: 100lm/W
- Life time: 50,000 hours
- Aluminum heat sink and PC cover
- Excellent heat dissipating, high standard stabilized power source
- Lumen maintenance at 70%: > 35,000 hours
- Input voltage: AC220V 50Hz
- Power factor: > 90%
- Color rendering index: >80Ra
- Large color temperature range from 3000K, 4000K and 6000K
- Beam angle: 140°
- Condition temperature: -20°C to +50°C
- Dimension: 600, 900, 1200 and 1500mm
- Environmental friendly: No Toxic material, No glass, no mercury, no UV and IR radiation
- Comply with safety standard EN60598, EN61347-2-13, EN62031, EN62471, EN62493 and EMC standard EN55015, EN61547, EN61000-3-2, EN61000-3-3
- CE standard and RoHS

## Applications:

-Offices, Shopping Centers, Car parks, Corridors, Staircases, Warehouses, Club houses, Universities , Residential areas, etc.

## Specifications:

Voltage	Power	Lumen	CRI	Color temp	Dimension	Life time
AC220V	9W	900 lm	80Ra	2700-6500K	600mm	50,000 hours
AC220V	14W	1400 lm	80Ra	2700-6500K	900mm	50,000 hours
AC220V	18W	1800 lm	80Ra	2700-6500K	1200mm	50,000 hours
AC220V	22W	2200 lm	80Ra	2700-6500K	1500mm	50,000 hours