

# T5 LED Tube

## No Re-wiring

## Compatibility with T5 electronic ballast

## Direct Retrofit type



### Features:

- Save up to 50% energy
- Plug in the existing T5 batten or T5 tray and no need to rewiring, no need internal T5 electronic ballast
- DIY within 1 minute to complete installation work
- Light efficiency: 100lm/W
- 50,000 hours life time
- SMD LED chips, with lumen depreciation <30% after 35,000 hours
- Color rendering index: 80Ra
- Large color temperature range from 3000K, 4000K,5000K, 6000K
- Beam angle: 140°
- Have transparent and frosted choice
- Condition temperature: -20°C to +50°C
- Humidity level: 0-90%
- Dimension: 549mm, 1149mm choice
- Environmental friendly: No Toxic material, No glass, no mercury, no UV and IR radiation
- Comply with international standard EN60598, EN55015, EN61547, EN61000-3-2, EN61000-3-3
- CE standard

### Applications:

-Offices, Shopping Centers, Car parks, Corridors, Staircases, Warehouses, Club houses, Universities , Residential areas, etc.

### Specifications:

Voltage	Power	Lumen	Color Temp	Life time	Dimension
AC220-240V	9W	900lm	2700-6500K	50,000 hours	600mm
AC220-240V	14W	1400lm	2700-6500K	50,000 hours	900mm
AC220-240V	17W	1700lm	2700-6500K	50,000 hours	1200mm
AC220-240V	25W	2500lm	2700-6500K	50,000 hours	1500mm